

DILOG



www.dilog.se

DILOG DCH-760 Twin Kabel/IP Hybrid

Ny kabel/IP hybrid box för Cryptoguard. Spela in två program samtidigt som du tittar på ett tredje ifrån hårddisken. Kan anslutas till TV via HDMI eller Scart. Användarvänlig meny gör boxen lätthanterad.

- Dubbla DVB-C Tuners
- Stöd för HD/SD (Mpeg2/Mpeg4 H.264)
- HDMI-utgång 1.4A
- Upplösning 576p,720p,1080i
- A/V-utgång
- Digital optisk ljudutgång
- 2xUSB 2.0 portar
- Anpassad för Cryptoguard
- USB 2.0 för inspelning på extern HDD*
- PVR Ready
- Låg förbrukning, under 1W i standby
- EPG-Elektronisk Program Guide
- TimeShift (med USB HDD ansluten)
- Föräldralås
- Snabbt kanalbyte
- Favoritlistor
- LCN-funktion, sorterar kanalerna rätt
- Flerspråksmenyer med svenska
- Text-TV
- Fast Ethernet RJ45+Wireless*
- Storlek: 192 x 38 x 150 mm
- Vikt: 0,42 kg

**option*

Technical Specification

Video Decoding

Transport Stream Profile Level	MPEG-2 ISO/IEC 1318-1 MPEG-2 MP@ML, MPEG-2 MP@HL, MPEG-4 AVC/H.264 HP@L4
Video Format	4:3, 16:9
Video System	PAL
Video Resolution	1080i, 720p, 576p

Audio Decoding

Audio Decoding	MPEG-1, Musicam Layers 1&2
Audio Mode	Single Channel, Dual Channel, Joint Stereo, Stereo
Sampling Rate	32, 44.1 & 48KHz

Chip & Memory

CPU	ST40 CPU Dual core : 450MHz 1600DMIPS
Flash Memory	64Mbyte
System Memory	DDR2 1Gbits x 2(256MB)
EEPROM	8Kbyte

Conditional Access Interface

CAS	CryptoGuard
Smart Card Reader	1 smart card reader

A/V & Data In/Out

RCA A/V HDMI	Video output, Audio L/R Digital Video and Audio output(HDMI / HDCP Certified by 1.4a)
Ethernet IR receiver	Fast Ethernet(10/100) Front side
USB	USB Ports 2.0 x2

Power Supply

Input Voltage	AC100-250V~, 50/60Hz, External Adpator
Power Consumption	Max.30W (Standby : Less than 1W)

Front Panel

Display	7 segment display
---------	-------------------

Physical Specification

Net Weight	420g
Gross Weight	850g (including all accessories)
Dimensions (WxHxD)	192x38x150 mm
Operating Temperature	0~50°C
Storage Temperature	-10~+60°C
Gift Box Size (WxHxD)	282x58x199
Master pack Size (WxHxD)	805x317x265 (14 pcs)

EAN

7 350 021 777 607

DILOG

Dilog Nordic AB
Faktorvägen 9, 434 37 Kungsbacka Sweden

Tel: +46 31 28 88 30
Fax: +46 31 28 82 33
www.dilog.se